


Velbon builds tripods of proven design with high quality standards for your everyday use.



- 2-Way Head (230 / 330 / Mini), 3-Way Head with a Quick Release Plate (330Q / Macro) for Photo & Video.
- Light weight, Slim 3-section legs (Mini / 2-section legs).
- Lift Elevator.
- Speedy leg locking system.
- Radial braces for secure set-up.
- Leg Foot Rubber for steadiness on variety of ground conditions.
- Tripod carrying case is included.



EX-Mini

2 WAYS

MAX	41.70	467
cm / inch	16.42	g / lbs
MAX	36.00	2.50
cm / inch	14.17	kg / lbs
MAX	19.00	1.50
cm / inch	7.48	kg / lbs
MAX	25.50	17
cm / inch	10.04	mm / inch

QUICK RELEASE
PLATE
QB-32

EX-Macro

3 WAYS

MAX	56.30	578
cm / inch	22.17	g / lbs
MAX	50.60	2.50
cm / inch	19.92	kg / lbs
MAX	20.30	1.50
cm / inch	7.99	kg / lbs
MAX	28.10	17
cm / inch	11.06	mm / inch

QUICK RELEASE
PLATE
QB-32

Full low angle position

EX-230

2 WAYS

MAX	122.00	2.00
cm / inch	48.03	kg / lbs
MAX	94.70	1.00
cm / inch	37.28	kg / lbs
MAX	43.50	17
cm / inch	17.13	mm / inch
MAX	744	865
g / lbs	1.64	g / lbs



EX-330

2 WAYS

MAX	145.00	2.00
cm / inch	57.28	kg / lbs
MAX	114.50	1.00
cm / inch	45.08	kg / lbs
MAX	50.60	17
cm / inch	19.92	mm / inch
MAX	828	865
g / lbs	1.83	g / lbs



EX-330Q

3 WAYS

MAX	146.00	2.00
cm / inch	57.48	kg / lbs
MAX	115.00	1.00
cm / inch	45.28	kg / lbs
MAX	50.60	17
cm / inch	19.92	mm / inch
MAX	865	865
g / lbs	1.91	g / lbs



EX-344Q

3 WAYS

MAX	155.00	2.00
cm / inch	61.02	kg / lbs
MAX	128.50	1.00
cm / inch	50.59	kg / lbs
MAX	48.50	20
cm / inch	19.09	mm / inch
MAX	1,155	1,155
g / lbs	2.55	g / lbs



EX-540

MAX	156.00	4.00
cm / inch	61.42	kg / lbs
MAX	129.50	2.00
cm / inch	50.98	kg / lbs
MAX	49.00	23
cm / inch	19.29	mm / inch
MAX	1,43	1,43
g / lbs	3.15	g / lbs



EX-630

MAX	168.00	5.00
cm / inch	66.14	kg / lbs
MAX	134.80	3.00
cm / inch	53.07	kg / lbs
MAX	61.50	26
cm / inch	24.21	mm / inch
MAX	1,69	1,69
g / lbs	3.73	g / lbs



EX-640

MAX	170.00	5.00
cm / inch	66.93	kg / lbs
MAX	142.80	3.00
cm / inch	56.22	kg / lbs
MAX	53.50	26
cm / inch	21.06	mm / inch
MAX	1,67	1,67
g / lbs	3.68	g / lbs



CX-888 BLACK

MAX	145.00	2.50
cm / inch	57.09	kg / lbs
MAX	121.00	1.50
cm / inch	47.64	kg / lbs
MAX	48.00	23
cm / inch	18.90	mm / inch
MAX	1.30	1.30
g / lbs	2.87	g / lbs



EX-430

MAX	151.00	2.00
cm / inch	59.45	kg / lbs
MAX	124.70	1.00
cm / inch	49.09	kg / lbs
MAX	56.00	20
cm / inch	22.05	mm / inch
MAX	1.20	1.20
g / lbs	2.65	g / lbs

QUICK RELEASE
PLATE
QB-46(DIN)

EX-440

MAX	153.00	2.00
cm / inch	60.24	kg / lbs
MAX	126.70	1.00
cm / inch	49.88	kg / lbs
MAX	47.00	20
cm / inch	18.50	mm / inch
MAX	1.18	1.18
g / lbs	2.60	g / lbs

QUICK RELEASE
PLATE
QB-46(DIN)

EX-888

MAX	153.00	3.00
cm / inch	60.24	kg / lbs
MAX	126.70	1.50
cm / inch	49.88	kg / lbs
MAX	48.50	23
cm / inch	19.09	mm / inch
MAX	1.29	1.29
g / lbs	2.84	g / lbs

QUICK RELEASE
PLATE
QB-46(DIN)

EX-530

MAX	156.00	4.00
cm / inch	61.42	kg / lbs
MAX	124.20	2.00
cm / inch	48.90	kg / lbs
MAX	57.00	23
cm / inch	22.44	mm / inch
MAX	1.45	1.45
g / lbs	3.20	g / lbs

QUICK RELEASE
PLATE
QB-46(DIN)

On EX-430 and higher, the camera plate turns to the right instead of left. This leaves left hand free to adjust tripod and camera controls while taking images in portrait mode. Importantly when using telephoto lenses the camera remains securely attached to plate due to effect of gravity tightening the screw connection.



From EX-430 through EX-640 All the heads are 3-way with Quick Release Plate & Friction Adjusting control. Elevator pole can be tightened and loosened with a quick turn.